



PREMIER-SERIES

9KCL & 9KFP

**9,000 LB.
CAPACITY**

FEATURES

- Single-Point Lock Release System
- 3" Diameter Hydraulic Cylinders
- Reinforced Carriages
- One-Piece Column Design
- Serviceable Arm Lock Gears
- Self-locking Arm Restraint Pins
- Padded Overhead Safety Shut-Off Bar
- Extra Large Door Guard Bumper Pads
- High-Durometer Rubber Lifting Pads
- Threaded Pad Mounts
- (4) 4" Stackable Pad Extensions
- Toe Guards For Each Lifting Arm
- Aircraft Quality 3/8" Diameter Steel Cables
- Multi-Ply Steel Braided Hydraulic Hoses
- Oversized 4-1/2" Cable Pulleys
- Serviceable Cylinder Pulley Bearings (grease fitting in shaft)
- Aluminum Self-Cooling Continuous-Duty Electric 220V Motor
- (10) 3/4" Concrete Wedge Anchor Bolt Kit
- 2 Year Electric/Hydraulic Warranty
- 5 Year Structural Warranty

CLEARFLOOR SPECIFICATIONS

Power Unit: 220V

Lifting Speed: 40-60 sec

Width: 132.25"

Height: 155"

Width Between Columns: 110.25"

Drive Thru Clearance: 102"

Lifting Height: 4" - 79"



HD2P-9KCL



HD2P-9KFP

FLOORPLATE SPECIFICATIONS

Power Unit: 220V

Lifting Speed: 40-60 sec

Width: 134.75"

Height: 111.25" *Carriage ladder will raise to 121.25" at max height*

Width Between Columns: 112.25"

Drive Thru Clearance: 103.25"

Lifting Height: 4" - 79"

TITANLIFTS.COM
888-908-4826