

### 9,000 LB. CAPACITY FEATURES



- Direct Drive Hydraulic Cylinders (9KMSC)
- Overhead Shut-off Bar w/Limit Switch (9KMSC)
- Chain Over Roller Hydraulic Cylinders (9KMSF)
- Serviceable Arm Restraint Locks
- Thread-up Lifting Pads
- Carriage Limit Switch
- 3-Stage Front Arms
- Single-Point Lock Release
- European Style Carriages
- 4" Truck Adapters
- Rubber Door Guards
- Steel Toe-guards
- Steel Hydraulic Oil Reservoir
- 5 Year Structural Warranty
- 2 Year Electric/Hydraulic Warranty
- Lifetime Warranty on Nylon Slide Blocks
- Durable Textured Powder-coated Finish

### CLEARFLOOR SPECIFICATIONS

Power Unit: 220V

Lifting Speed: 50-60 sec

Width Between Columns: 111.5"

Drive Thru Clearance: 100.75"

Min/Max Pad Height: 3.75" - 81.75"

Baseplate to Baseplate Width: 134.25"

Column Height: 140.5"

\* CYLINDERS WILL EXTEND 7" THROUGH THE TOP PLATES WHEN LIFT IS RAISED TO MAX HEIGHT.



HD2P-9KMSC



HD2P-9KMSF

### FLOORPLATE SPECIFICATIONS

Power Unit: 220V

Lifting Speed: 50-60 sec

Width Between Columns: 111.5"

Drive Thru Clearance: 100.75"

Min/Max Pad Height: 3.75" - 80.25"

Baseplate to Baseplate Width: 134.25"

Column Height: 112"

\* CARRIAGE LOCK LADDER WILL EXTEND 10" ABOVE TOP OF COLUMN WHEN RAISED TO MAX HEIGHT.

TITANLIFTS.COM  
888-908-4826