



8000 & 8000XLT



**8,000 LB.
CAPACITY**

INCLUDES

- Jack Tray
- Steel Ramps
- Three Drip Trays
- Caster Kit



OPTIONAL

- Sliding Bridge Jack
- Aluminum Ramp Upgrade



FEATURES

- Aircraft quality cables rated at 14,500 lb
- 18-5/8" wide runways formed with one-piece 3/16" non-skid diamond plate
- Single point safety lock release handle located near power unit
- Large 3" diameter cylinder
- Powder coated in midnight black finish
- Diamond plated steel approach ramps
- Primary locking system with secondary slack safety lock
- 5 Year Structural Warranty
- 1 Year Electric/Hydraulic Warranty

SPECIFICATIONS

- Power Unit: 110V/3HP/20AMP**
- Length: 175-1/2"**
- Width w/Power Unit: 114-3/4"**
- Height(min): 86-7/8"**
- Width Between Columns: 94-3/8"**
- Lifting Height: 4-3/4" - 74-3/4"**
- Between Runways: 37-1/2"**
- Runway Width: 18-5/8"**
- Runway Length: 165-1/2"**
- Ramp Length: 37"**

XLT SPECIFICATIONS*

- Length: 190-1/2"**
- Height(min): 94-3/4"**
- Width w/Power Unit: 120-3/4"**
- Width Between Columns: 100-3/8"**
- Between Runways: 43-1/4"**
- Lifting Height: 4-3/4" - 82-1/4"**
- Runway Length: 180-1/2"**

*INCLUDES ONLY SPECS THAT DIFFER FROM THE SDPL-8000 MODEL



SDPL-8000XLT SHOWN

TITANLIFTS.COM
888-908-4826